



Bathroom and Kitchen Paint

- for indoor surfaces at risk of mould
- washable, breathable protective paint



Application rate	Ca. $1\ \text{l/f}\ \text{m}^2$. Determine the exact coverage by applying a test coat to the object
Areas of use	 For interior For low-odour, washproof interior coatings in kitchens, bathrooms, basements, garages and storage rooms
Property profile	 Washproof, solvent-free special paint with long-lasting integrated film protection Wet abrasion resistance class III DIN EN 13300 and hiding power class II DIN EN 13300 at 7 m2 per litre
Directions	*Contains the biocidal ingredient octylisothiazolinone to protect the film from mould infestation. The product must always be used according to the instructions on the label (and the Technical Data Sheet). A dry, firm and stable substrate is required for all coating work Minimum working temperature for material and substrate: + 5°C Establish the cause of the mould infestation and treat Remove mould by cleaning with water and with mould remover if necessary, and leave to dry Two undiluted coatings increase the mould resistance of the paint Drying: surface dry after 2 hours, can be overcoated after 6 hours, load-bearing after 3-5 days. Drying times may be longer at low temperatures
Notes	*Contains the biocidal ingredient octylisothiazolinone to protect the film from mould infestation. The product must always be used according to the instructions on the label (and the Technical Data Sheet). Please secure the container against falls and spills during transport. Stir well before use!
Tools / Cleaning	Clean the tools immediately after use with warm water Apply with roller and brush
Storage / Shelf life	Store in the sealed original container in a cool, dry, and frost-free place. Can be used for at least 1 year after the date of purchase
Disposal	P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
VOC content as per the "Decopaint" Directive (2004/42/EC)	EU limit value for the product (Cat. A/a): max. 30 g/l (2010). This product contains $<$ 1 g/l VOC.
Precautionary statements / Hazard statements	warning P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P273 Avoid release to the environment. P280L Wear protective gloves/protective clothing/eye protection/face protection. P302+P352B IF ON SKIN: Wash with plenty of soap and water. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P501A Dispose of contents/container in accordance with local/regional/national/international regulations. H317 May cause an allergic skin reaction. H412 Harmful to aquatic life with long lasting effects.

Precautionary statements / Hazard statements

BAUFIX Gmbh • www.baufix-online.de 808130 TM-3 08/22 1/1

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.