



Wood Sealing Primer

- blocks wood ingredients reliably
- for softwoods and hardwoods
- water-based special paint

Application rate	Approx. 2 x 80 ml/m. Determine the exact coverage by applying a test coat to the object
Areas of use	<ul style="list-style-type: none">■ Pine and deciduous woods outdoors which are still to receive a final coat, such as fences, timber frames, folding shutters, windows, doors, etc.■ Do not use on freshly waterproofed wood
Property profile	<ul style="list-style-type: none">■ Moisture-regulating and waterproof
Directions	<p>The substrate must be clean, dry and stable Pre-treat untreated exterior wood with a wood preservative (use wood preservatives safely. Always read the label and product information before use.) Application temperature: +5°C to +25°C Apply 2 coats with a light sanding in between the coats Drying: approx. 2-4 hours. Paint film fully hardened after approx. 2 weeks Intermediate and final coats of suitable products can be applied after drying. Protect the fresh coat from rain Check the compatibility, adhesion and insulating effect with the substrate by applying onto a test area Stir well, then apply promptly and without dilution in the grain direction</p>
Notes	<p>Please secure the container against falls and spills during transport. For more information, you can obtain the relevant Technical Data Sheet from www.baufix-online.com</p>
Tools / Cleaning	<p>Clean tools immediately after use with water and detergent Dispose of cleaning residues properly</p>
Storage / Shelf life	Store in the sealed original container in a cool, dry, and frost-free place. Can be used for at least 1 year after the date of purchase
Disposal	P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
Biocidal Products Regulation	Contains a biocidal product (in-can preservative) with the biocidal agents CMIT/MIT (3:1) for protecting the container content from deterioration by microbial organisms (germs, yeast, etc.). Please note the processing guidelines carefully!
Safety advice	<p>Keep out of the reach of children. Use an A2/P2 combi-filter when spraying. Use a P2 dust filter when grinding or sanding. Ensure the area is thoroughly ventilated during application and drying. Do not eat, drink or smoke while using the paint. In the event of contact with the eyes or skin, rinse out thoroughly and immediately with water. Do not allow it to enter the ground, the sewage system or any bodies of water. Clean tools with soapy water immediately after use. Only send fully emptied containers for recycling. Take any leftover liquid material to the collection point for waste paint.</p>
VOC content as per the "Decopaint" Directive (2004/42/EC)	EU limit value for the product (Cat. A/g): max. 30 g/l (2010). This product contains < 30 g/l VOC.
Precautionary statements / Hazard statements	Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2- methyl-2H-isothiazol-3- one (3:1). May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Precautionary statements / Hazard statements	

